

MPL-III-656.5/1~2uJ/1-5mW




**LD PUMPED ALL-SOLID-STATE  
Q-SWITCHED LASER AT 656.5**

All solid state Q-switched laser at 656.5 nm has the features of high peak power, high repetition rate, and short pulse duration, which is widely used in medical, scientific research, industry and so on.




SPECIFICATIONS

Wavelength (nm)	656.5 ± 1	
Operating mode	Q-switched pulsed laser	
Single pulse energy (μJ)	1~2	
Pulse duration (ns)	~15	
Peak power (W)	~100	
Rep. rate (kHz)	Controllable	Specified One rep. rate, such as 1k, 2kHz, with stable laser pulses emitting (stable pulse energy, peak, duration and period). Different rep. rate in the range of 1Hz-2kHz can be obtained by input an external TTL signal.
	Uncontrollable	QCW state with one rep. rate between 2kHz-3kHz.
Average power (mW)	Average power (mW) = Single pulse energy (μJ) * Rep. rate (kHz)	
Ave power stability (over 4 hours)	<1%, <3%, <5%	
Transverse mode	TEM <sub>00</sub>	
Warm-up time (minutes)	<10	
M <sup>2</sup> factor	<1.2	
Beam divergence, full angle (mrad)	<1.5	
Beam diameter at 1/e <sup>2</sup> (mm)	~1.2	
Beam height from base plate (mm)	24.8	
Operating temperature (°C)	10~35	
Power supply (90-264VAC)	PSU-III-FDA	
Expected lifetime (hours)	10000	
Warranty period	1 year	




MPL-III-656.5



140.8(L) × 73(W) × 46.2(H) mm<sup>3</sup>, 0.6kg

PSU-III-FDA



171 (L) × 130(W) × 65 (H) mm<sup>3</sup>, 1.2kg