

PGL-D8-520



PGL-D8 high power green laser module at 520nm is made features of small size, high output power, long lifetime, which made it be used widely in collimation, laser medical treatment, scientific experiment, optical instrument and so on.

SYSTEM SPECIFICATIONS*

Wavelength	nm	520
Wavelength tolerance	nm	±5
Output power	mW	1-30
Operating mode		CW
Transverse mode		Near TEM ₀₀
Beam diameter at the aperture(1/e ²)	mm	~3.5
Beam divergence, full angle	mrad	<1
Expected lifetime	hours	10,000
Warranty	months	6

ELECTRICAL SPECIFICATIONS

Operating voltage(external PCB1)	7VDC
Operating voltage(external PCB2)	5VDC(TTL30K or Analog 0-3V,0-5V)
Operating voltage(external PCB3)	5-12VDC(TTL30K and Analog 0-3V,0-5V)
Connection	Cable with flying leads

ENVIRONMENTAL CONDITIONS


Operating temperature	0°C to 40°C
Storage temperature	-20°C to 80°C
Humidity	< 90%, non-condensing
Dissipated heat	< 2.2W

MECHANICAL SPECIFICATIONS


Laser head diameter Φ	mm	8
Length	mm	15
Material		Aluminum
Shell polarity		The housing has non-polarity

*All testing data under the conditions of temperature 25°C.


Dimensions of laser($\Phi 8 \times 15 \text{mm}^2$)



Dimensions of PCB1(*small size*, $9 \times 12 \text{mm}^2$, 7V)



Dimensions of PCB2($11 \times 25 \text{mm}^2$, DC5V, TTL or Analog)



Dimensions of PCB3($20 \times 30 \text{mm}^2$, DC5-12V, TTL and Analog)

