

MBL-III-473/1~150mW


## LD PUMPED ALL-SOLID-STATE BLUE LASER



All solid state 473nm blue laser is made features of ultra compact, long lifetime, low cost and easy operating, which is used in fluorescence sensors, Raman spectrum, laser printing, holography, laser display, submarine communication, biomedicine, laser lighting show, etc.



### SPECIFICATIONS

Wavelength (nm)	473±1			
Output power (mW)	>1, 5, 10, ... , 150			
Transverse mode	TEM <sub>00</sub>			
Operating mode	CW			
Power stability (rms, over 4 hours)	<3%, <5%, <10%			
Warm-up time (minutes)	<10			
M <sup>2</sup> factor	<1.2			
Beam divergence, full angle (mrad)	<1.5			
Beam diameter at the aperture (mm)	~2.0			
Beam height from base plate (mm)	24.8			
Polarization ratio	>100:1 (0 or 90 degree)			
Noise of amplitude (rms, 1~20MHz)	~30%			
Operating temperature (°C)	10~35			
Power supply (90-264VAC or 5V DC)	PSU-III-LCD	PSU-III-LED	PSU-III-FDA	PSU-III-OEM
Modulation option	TTL on/off, 1Hz-1KHz, 1KHz-10KHz, 10KHz-30KHz; and Analog modulation option			
Expected lifetime (hours)	10000			
Warranty period	1 year			



MxL-III-473	PSU-III-LCD <i>High stability!</i>	PSU-III-LED	PSU-III-FDA	PSU-III-OEM
 140.8(L)×73(W)×46.2(H) mm <sup>3</sup> , 0.6kg	 153 (L) ×155(W) ×92 (H) mm <sup>3</sup> , 1.4kg	 154 (L) ×155(W) ×95 (H) mm <sup>3</sup> , 1.5kg	 133 (L) ×130(W) ×65 (H) mm <sup>3</sup> , 1.2kg	 100 (L) ×60(W) ×56 (H) mm <sup>3</sup> , 0.2kg
				