

MGL-W-589/800~4500mW




LD PUMPED ALL-SOLID-STATE YELLOW LASER AT 589nm




All solid state 589 nm yellow laser is made features of ultra compact, long lifetime and easy operating, which is widely used in collimation, laser medical treatment, scientific experiment, optical instrument, etc.



SPECIFICATIONS

Wavelength (nm)	589±2	
Operating mode	CW	
Output power (mW)	>800, 850, 900, ..., 4500	
Power stability (rms, over 4 hours)	<3%, <5%, <10%	
Transverse mode	Near TEM ₀₀	
Beam divergence, full angle (mrad)	<2.0	
Beam diameter at the aperture (mm)	~5.5	
Warm-up time (minutes)	<10	
Beam height from base plate (mm)	93.5	
Operating temperature (°C)	10~35	
Power supply (90-264VAC)	PSU-W-LED	PSU-W-FDA
TTL / Analog modulation	TTL or Analog with 1Hz-1kHz 1kHz-10kHz, 10kHz-30kHz optional	
Expected lifetime (hours)	10000	
Warranty period	1 year	



MxL-W-589	PSU-W-LED	PSU-W-FDA
 <p>346 (L) ×140 (W) ×125 (H) mm³, 5.7 kg</p>	 <p>336 (L) ×168 (W) ×133 (H) mm³, 4.6 kg</p>	 <p>307 (L) ×168 (W) ×123 (H) mm³, 4.5 kg</p>