

MLL-III-510/1~30mW

SPECIFICATIONS

LOW NOISE GREEN LASER  
MODULE AT 510 nm

Green laser module at 510 nm is made features of ultra compact, long lifetime, and easy operating, which is widely used in biological, medical, laser pumping, scientific research, etc.



Wavelength (nm)	510±5	
Output power (mW)	>1, 2, 3, ...30	
Transverse mode	Near TEM <sub>00</sub>	
Operating mode	CW	
Power stability (rms, over 4 hours)	<1%, <3%, <5%	
Spectral linewidth (nm)	~0.5	
Noise of amplitude (pk-pk, 1~20MHz)	<1%	
Coherent length (cm)	>20	
Warm-up time (minutes)	<5	
Beam divergence, full angle (mrad)	1.0	
Beam diameter at the aperture (mm)	3.0	
Beam height from base plate (mm)	24.8	
Pointing stability after warm-up (mrad)	<0.05	
Operating temperature (°C)	10~35	
Power supply (90-264VAC)	PSU-III-LED	PSU-III-FDA
Expected lifetime (hours)	10000	
Warranty period	1 year	



MxL-III-510	PSU-III-LED	PSU-III-FDA
 <p>140.8(L)×73(W)×46.2(H) mm<sup>3</sup>, 0.6kg</p>	 <p>154 (L) ×155(W) ×95 (H) mm<sup>3</sup>, 1.5kg</p>	 <p>133 (L) ×130(W) ×65 (H) mm<sup>3</sup>, 1.2kg</p>
		