



MRL-FN-660/200~400mW



**LD PUMPED ALL-SOLID-STATE
RED LASER AT 660nm**

DPSS red laser at 660nm is made features of ultra compact, long lifetime, low cost and high stability, which is widely used in measurement, spectrum analysis, and scientific research etc.



SPECIFICATIONS

Wavelength (nm)	660±1
Operating mode	CW
Output power (mW)	>200, 250, 300, ... , 400
Power stability (rms, over 4 hours)	<3%, <5%, <10%
Transverse mode	Near TEM ₀₀
M ² factor	<1.2
Beam diameter at the aperture (1/e ² , mm)	~2.0
Beam divergence, full angle (mrad)	<1.5
Polarization ratio	>100:1 Horizontal ±5 degree (Vertical Optional)
Warm-up time (minutes)	<10
Pointing stability after warm-up (mrad)	<0.05
Beam height from base plate (mm)	27.4
Operating temperature (°C)	10~35
Power supply (90-264VAC)	PSU-H-LED PSU-H-FDA
Expected lifetime (hours)	10000
Warranty	1 year



Note: The laser head needs to be used on a heat sink with good heat dissipation.

MRL-FN-660	PSU-H-LED	PSU-H-FDA
<p>197(L)×70(W)×50(H) mm³, 2.0 kg</p>	<p>277 (L) ×145(W) ×106 (H) mm³, 2.6 kg</p>	<p>236(L) ×145(W) ×104(H) mm³, 2.3 kg</p>