



MSL-FN-656.5/1~50mW

SINGLE LONGITUDINAL MODE RED LASER AT 656.5nm

All solid state single longitudinal mode red laser at 656.5nm is made features of ultra compact, long lifetime, low cost and easy operating, which is used in DNA sequencing, flow cytometry, cell sorting, optical instrument, spectrum analysis, interference, measurement, holography, brillouin scattering, physics experiment, etc.




SPECIFICATIONS

Wavelength (nm)	656.5±1
Operating mode	CW
Output power (mW)	>1, 5, 10, 20, ... , 50
Power stability (rms, over 4 hours)	<1%, <3%, <5%
Transverse mode	TEM ₀₀
Longitudinal mode	Single
Spectral linewidth (nm)	<0.00001
Coherent length (m)	>50
Noise of amplitude (rms, 1Hz~20MHz)	<1%, typical<0.5%
M ² factor	<1.2
Beam diameter at the aperture (1/e ² , mm)	<2.0
Beam divergence, full angle (mrad)	<1.2
Polarization ratio	>100:1, Vertical±5 degree (Horizontal Optional)
Warm-up time (minutes)	<10
Pointing stability after warm-up (mrad)	<0.05
Beam height from base plate (mm)	27.4
Operating temperature (°C)	15~35
Power supply (90-264VAC)	PSU-H-FDA
Expected lifetime (hours)	10000
Warranty	1 year




MXL-FN-656.5



197(L)×70(W)×50(H) mm³, 1.5 kg

PSU-H-FDA



275(L)×145(W)×104(H) mm³, 2.3 kg