



OEM-XD-447/9-20W

### OEM BLUE DIODE LASER AT 447nm

OEM diode laser 447 nm blue laser is made features of ultra compact, long lifetime, low cost and easy operating. It's easy to be installed in customer's equipment.



#### SPECIFICATIONS

Wavelength (nm)	447±5		
Output power (W)	>9, >12	>16, >20	
Operating mode	CW		
Power stability (rms, over 4 hours) at 25°C	<1%, <3%, <5%		
Beam diameter at the aperture (mm)	~7×5	~7×7	
Beam divergence, full angle (mrad)	<1.4×0.8		
Polarization direction	Horizontal+ Vertical		
Warm-up time (minutes)	<5		
Beam height from base plate (mm)	30 (OEM-XD-447)	68.2(XD-447-HS)(9~12W)	93.5(XD-447-HS)(9~20W)
Operating temperature (°C)	25+/-3 (OEM-XD-447)	10-35 (XD-447-HS)	
Power supply(90-264VAC or 12VDC15A,)	PSU-6R-OEM/ PSU-6R-OEM-H		
Modulation option	TTL/Analog 1Hz-5KHz, 1Hz-10KHz, 1Hz-100KHz, and TTL on/off		
Expected lifetime (hours)	10000		
Warranty	1 year		



OEM-XD-447	XD-447-HS	XD-447-HS	PSU-6R-OEM	PSU-P-OEM-H	Adapter (20W)	Adapter (10-16W)
<p>189.5(L)×166(W) ×48(H) mm<sup>3</sup>, 2.7kg</p>	<p>288(L)×186(W)×111.8(H) mm<sup>3</sup>, 4.9kg</p>	<p>238(L)×184(W) ×86.2(H) mm<sup>3</sup>, 4 kg</p>	<p>120(L)×65(W) ×29(H) mm<sup>3</sup>, 0.5 kg</p>	<p>140(L)×80(W) ×67(H) mm<sup>3</sup>, 1 kg</p>	<p>195(L)×86(W) ×36.5(H) mm<sup>3</sup>, 0.6kg</p>	<p>177.5(L)×62(W) ×30(H) mm<sup>3</sup>, 0.5kg</p>