



## SLDP-785-30-SM

### ■ Features

- 785nm
- With 9um Fiber
- Coaxial or B1 Package
- Built-in PD



### ■ Absolute Maximum Ratings

Parameter	Symbol	Value	Unit
Reverse Voltage	Vr	2.0	V
Operating Temperature	Top	-10 ~ +60	°C
Storage Temperature	Tstg	-40 ~ +85	°C
Lead Soldering Temperature (10sec)	Tis	260	°C

### ■ Initial Electrical/Optical Characteristics

Item	Symbol
Center Wavelength @ 25°C	785±5nm
Output Power	30mW
Fiber Type	SMF-28
Fiber Core	9um
Monitor Current	1mA
PD Reverse Voltage	30V
Recommend Operating Temperature	25°C
Fiber Connector	FC/SC/SMA905
Fiber Length	80cm
Threshold Current (Typ.)	30mA
Operating Current (Typ.)	140mA
Operating Voltage	2.0V
Package Style	Coaxial or B1
Photodiodes	Built-in

CHANGCHUN NEW INDUSTRIES  
OPTOELECTRONICS TECH.CO.,LTD.

CHANGCHUN NEW INDUSTRIES  
OPTOELECTRONICS TECH.CO.,LTD.




electronics Tech. Co., Ltd ◆ CONTACT

No.888, Jinhua Road, High-tech Zone, Changchun  
130103, China


Phone: +86-431-87033597

Fax: +86-431-87033597


## Coaxial Package View



## B1 Package View



## PIN Bottom View



1	LD(-)
2	LD(+)&PD(-)
3	PD(+)



Changchun New Industries Optoelectronics Tech. Co., Ltd  
<http://www.cnilaser.com>

### ◆ CONTACT

No.888, Jinhu Road, High-tech Zone, Changchun  
 130103, China

Phone: +86-431-87033597

Fax: +86-431-87033597