



MGL-U-xxx-SF series

DPSS LASER

All solid-state CW mode laser is made features of ultra compact, easy operating, high power and stability, which is perfect for flow cytometry, spectrum analysis, microscopy, semiconductor inspection, cell sorting, optical instrument, , physics experiment, etc.



SPECIFICATIONS

Wavelength (nm)	501±1	505±1	571±1	582±2	594±1	597±1
Operating mode	CW					
Output power (mW)	1-200	1-100	1-200	1-100	50-1500	1-120
Power stability (rms, over 4 hours)	<5%, <3%					
Transverse mode	Near TEM ₀₀					
Beam diameter at the aperture (1/e ² , mm)	~3		~4		<3.5	~4
Beam divergence (mrad)	<1		<3		~5	<3
Cooled method	Fan Cooled/ Water Cooled					
Warm-up time (minutes)	<10					
Beam height from base plate (mm)	91@Fan Cooled/ 55@Water Cooled					
Operating Temperature (°C)	15-30					
Power supply (90-264VAC)	PSU-W-FDA					
Expected lifetime (hours)	10000					
Warranty	1 year					



LASER HEAD (Fan Cooled)	LASER HEAD (Water Cooled)	POWER SUPPLY (PSU-W-FDA)
<p>256(L) × 156(W) × 121(H) mm³</p>	<p>239.5(L) × 165(W) × 85(H) mm³</p>	<p>307 (L) × 168(W) × 123(H) mm³, 4.5kg</p>